













HERADESIGN® Superfine



HERADESIG® Superfine is a single layer magnesite bonded wood wool acoustic ceiling and wall panel (fibre width 1mm).

- Building biology recommended
 Cradle to Cradle Certified[®] Gold for white and natural colours only

knaufceilingsolutions.com

HERADESIGN® Superfine



System	A2.1	, A2.2		B2.1, B2.2								C2.1		\$2.1	
	VK-09			GK		AK-02/5		AK-03		SK-04		1	SY-02		
Edge details	VK-10			AK-00		AK- 02/10				SK-05					
_		- VK-10/	/5	AK-01		AK-				SK-06					
· · · ·															
Dimensions [mm]	600 x 600, 625 x 625, 1200 x 600, 1250 x 625, additional sizes on request.														
Thickness [mm]	7.8				25						35				
Weight [kg/m²]			12.6						16.5						
Sound absorption	Thickness [mm]	TCH [mm]	HERADESIGN [mm]	Acoustic lining [kg/m³]	125	250	requencie 500	s [Hz], α 1000	2000	4000	Entire NRC	e range $\alpha_{_{ m w}}$	Class	s (//////	
	25 25	55 55	0 25	90	0.10	0.20	0.45 1.00	0.70	0.55	0.75 1.00	0.50	0.45 (MH) 0.85 (H)	D B	- 뒫	
	25 25	200	0 25	0 90	0.25 0.45	0.65	0.70	0.60	0.75 0.95	0.90	0.70	0.70 (H) 1.00	C A	1 ₩₩₩₩	
Sound Attenuation		D _{nfw} up to 30 dB according to DIN EN ISO 10848-2:2006													
Ball impact safety	Ball impact resistant according to DIN 18 032 / part 3 or class 1A according to EN 13964 annex D														
	Ceiling panelling system B2.1, B2.2, C2.1 Wall panelling system B2.1, B2.2, S2.1														
Fire resistance class	El 30 (a←b)														
Fire reaction	Euroclass B-s1,d0														
Thermal conductivity	λ = 0.09 W/mK according to EN 12667														
Humidity resistance	Suitable for rooms with a constant humidity of up to 90%. For applications where there is a constant relative air humidity in excess of 80%, expert advice for building physics is recommended.														
Cleanability															
Sustainability	WWW.bloure-engel.de/1/2132														
Area of application				effective suspe ironmental inf						interior	spaces a	s well as roo	ofed out	door areas that	
Installation	The installation of HERADESIGN® acoustic panels should take place during the last phase of the job, and in temperature and humidity controlled conditions. All building activities which create dust must be completed before the start of installation. Store the panels flat and protect against moisture and dirt. The packaging does not protect the products against rain. HERADESIGN® products should be installed in strict accordance with Knauf Ceiling Solutions installation and storage guidelines.														
Designation code	WW-EN 13168-L4-W2-T2-S2-P2-Cl3														
Special information		 Manufacturing tolerances in nominal dimensions: L4, W2, T2: ± 1mm, for lengths > 1250mm L4: ± 2mm Maximum changes in dimension in standard climate 23°C/50% relative humidity: ± 1% 													
		hite RAL 9010		Beige ral tone 13	Pas	itel col	ours	So	lid col	ours	Meto	allic colou	's S	pecial colours	
Colours	 The unique and natural structure of HERADESIGN® wood wool makes it an ideal solution for projects requiring creative colour schemes. Choose from an almost unlimited range of popular RAL and NCS colour systems. Deviations in colour and visual appearance may occur due to the rough fibre and panel surface 														
		War.								Meallin				28	

Products may vary from country to country. Please contact your local sales representative. For further information and legal notice, please visit our website.